

EPC-E3940-3S2E6U1V1H

Fanless BOX PC Intel Atom X5-E3840 1.8GHz, HDMI, VGA, 2xGbit Lan, 6x USB, 3x COM serial port FEATURES

- Intel Atom® x5-E3940 on board
- 204-pin DDR3L-1866 SO-DIMM for up to 8 GB of memory
- Supports 2 GbE LAN
- 3 COM
- 6 USB
- Supports one 2.5" SATA drive bay and mSATA
- Trusted Platform Module (TPM) 2.0
- 2 PCI Express Mini Card slots and 1 SIM slot
- 40°C to +60°C operating temperature range
- Hailo-8™ AI acceleration modules compatible
- Additional accessories: Must be ordered alongside:
Wall mounting kit, VESA mounting kit, DIN rail kit
- OS support: Win10 IoT, Linux
- 9 to 36 VDC



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

SPECIFICATIONS

CPU	:	Intel® Atom® Processor x5-E3940 1.8 GHz
Chipset	:	SoC Integrated
USB	:	4 x USB 3.0, 2 x USB 2.0
Operating Temp.	:	-40°C to +60°C (-40°F to +140°F) (with W.T. SSD/DRAM for 9 to 36 VDC) (Default: Turbo mode)
Andet	:	1 x Phoenix type VDC power input connector 4 x SMA-type antenna connector 1 x AT/ATX switch 1 x ATX power switch
BIOS	:	AMI
Approval	:	CE, FCC Class A
Chok/Vibration	:	Vibration IEC 60068-2-27 (with SSD: 50G, half-sine, 11 ms duration) Shock IEC 60068-2-64 (with SSD: 3Grms STD, random, 5 to 500 Hz, 1 hr/axis)
Ethernet	:	2 x 10/100/1000 Mbps Ethernet (Intel® i211-AT)
Forsyning	:	9 to 36 VDC
Hukommelse	:	1 x 204-pin DDR3L-1866 SO-DIMM, up to 8GB
IP-Tæthed	:	IP40





EPC-E3940-3S2E6U1V1H

SPECIFICATIONS

Materiale	:	Aluminum extrusion and heavy-duty steel, IP40
Montering	:	Wall mount Kit VESA mount kit DIN-rail kit
Msata	:	1 x mSATA (enabled in BIOS setting)
Mål og vægt	:	1.6Kg
OS SUPPORT	:	Win10 IoT, Linux Software , AXView
Porte	:	2 x RS-232/422/485 1 x RS-232
SIM kort	:	1 x SIM slot
Udgange	:	1 x HDMI (lockable) 1 x VGA
VESA standard	:	yes
Watchdog	:	65536 levels, 1 to 65535 sec.
Dimensioner	:	(W x D x H) 200 x 120 x 46 mm (7.87" x 4.72" x 1.81")

