

IP67 Waterproof GPU Computer Supporting NVIDIA® RTX A2000/ Tesla T4/ Quadro P2200 with All M12 Connectors

FEATURES

- IP67 waterproof GPU computer with NVIDIA® RTX A2000/ Tesla T4/ Quadro P2200
- Intel® Xeon® E or 9th/ 8th-Gen Core™ i7/ i5/ i3 CPU
- Patented waterproof 2U 19" chassis for rack or wall-mount*
- Guaranteed non-throttling GPU performance up to 62°C ambient
- Up to eight 802.3at Gigabit PoE+ ports via M12 X-coded connectors
- VGA, USB 2.0 and COM ports via M12 A-coded connectors
- 8~48V wide-range DC input with built-in ignition power control
- MIL-STD-810G and EN 50155 certified
- *R.O.C Patent No. I697759, *CN Patent Pending





SPECIFICATIONS

CPU	:	Supporting Intel® Xeon® E and 9th/ 8th-Gen CPU (LGA1151 socket) - Xeon E 2278GE (8C/16T) / 2278GEL (8C/16T) / 2176G (6C/12T) - i7-9700E, i7-9700TE, i7-8700, i7-8700T - i5-9500E, i5-9500TE, i5-8500, i5-8500T - i3-9100E, i3-9100TE, i3-8100, i3-8100T
Chipset	:	Intel® C246 platform controller hub
USB	:	from 3 to 5 USB depends on solution contact our sales
Operating Temp.	:	with 35W CPU -25°C ~ 70°C **** with >= 65W CPU -25°C ~ 70°C ***/ **** (configured as 35W TDP mode) -25°C ~ 50°C ***/ **** (configured as 65W TDP mode)
Approval	:	EN-50155, CE/FCC Class A, according to EN 55032 & EN 55035
Chok/Vibration	:	Vibration MIL-STD-810G, Method 514.7, Category 4 Shock MIL-STD-810G, Method 516.7, Procedure I
Ethernet	:	Optional: 1x 10 GbE port by Intel® X550AT controller (M12 X-coded) contact DANBIT A/S
Forsyning	:	8V to 48V DC input (M12 S-coded) Ignition Control Built-in ignition power control (IGN/ GND signal via M12 serial port connector)
Grafik	:	Integrated Intel® UHD Graphics 630
Hukommelse	:	Up to 64 GB ECC/ non-ECC DDR4-2666/ 2400 SDRAM(two SODIMM sockets)
Luftfugtighed	:	10%~90% , non-condensing
Lyd	:	depends on solution contact sales





SPECIFICATIONS

Msata	:	2x full-size mSATA port (mux with mini-PCIe)
Mål og vægt	:	depends of solution from 12 to 12.2Kg
PoE	:	1x IEEE 802.3at (25.5W) Gigabit PoE+ ports by Intel® I219 (M12 X-coded) 3x IEEE 802.3at (25.5W) Gigabit PoE+ ports by Intel® I210 (M12 X-coded) 7x IEEE 802.3at (25.5W) Gigabit PoE+ ports by Intel® I210 (M12 X-coded)
Udgange	:	1x VGA (M12 A-coded), supporting 1920 x 1200 resolution
AMT	:	Supports AMT 12.0
Dimensioner	:	440mm (W) x 310mm (D) x 86.5mm (H) (excl. rack-mount bracket)

