

6 ports Managed switch, 4 x RJ45
10/100/1000/2500Mbps, 2 x SFP slot 1000/2500Mbps.
9-48VDC, 24VAC.

FEATURES

- 4 x 10/100/1G/2.5GBASE-T RJ45 copper ports
- 2 x 10GBASE-SR/LR SFP+ slots, compatible with 1G/2.5GBASE-X SFP
- 1 x RJ45-to-RS232 console interface for basic management and setup
- DC 9 to 48V input or AC 24V input
- DIN-rail and wall-mountable designs
- IP30 aluminum case
- Temperature -40 to +75 degrees C
- 2 x digital input (DI)
- 2 x digital output (DO)
- Integrates sensors into auto alarm system
- Transfers alarm to IP network via email and SNMP trap
- IPv4 dynamic routing protocol supports RIPv2 and OSPFv2
- IPv6 dynamic routing protocol supports OSPFv3
- IPv4/IPv6 hardware static routing
- Supports G.8032 ERPS (Ethernet Ring Protection Switching)
- IEEE 1588v2 PTP (Precision Time Protocol) transparent clock mode
- Supports IPv4 IGMP snooping v1, v2 and v3
- Supports IPv6 MLD snooping v1 and v2
- Switch Management Interfaces
- SNMP Management

