



Svensk Binär Teknik

MON15-IP66-STEEL

15" IP66 TFT screen 6-sided Fully IP66 sealed
Capacitive touch, 1800 nits in stainless steel for
sunlight UV protection !

FEATURES

- 15" TFT 1024x768@60Hz
- 4:3 - XGA
- PCAP Touch (optional Resistive touch), USB
- 1000 nits
- Robust, reliable and good performance
- 6-sided IP66 tight
- VGA and HDMI inputs
- Optical bonding (Optical Bonding), UV protection
- SS 304 steel cabinet
- VESA Mount 100 mm
- Input voltage: 9 - 36VDC
- Optional 110-230VAC built-in power supply
- Cables with waterproof connectors included
- Temperature: -10 - +60°C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Operating Temp.	:	Operating: 0°C to 60°C Storage: -20°C to 60°C, (special version can be ordered for WT)
Approval	:	CE, ROHS
Betjening	:	OSD-Multi Language
Forsyning	:	Input Voltage DC: 12V (Options DC36-9V/AC110-230V)
I/O	:	VGA, HDMI
IP-Tæthed	:	IP66
Kontrast	:	700:1
Luftfugtighed	:	Operating: 10% to 90% (No Condensation)
Lyd	:	OPTION!
Materiale	:	Stainless Steel
Opløsning	:	1024x768@60Hz
Touch	:	resistive, PCAP, non. No touch as standard





Svensk Binär Teknik

MON15-IP66-STEEL

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.