



Svensk Binär Teknik

VTL100038

DC Voltage Monitor 15V

FEATURES

- Compact and efficient DC voltage monitor for systems up to 15V
- Voltage Measurement 0-15V
- Operating Temperature -10° C to +80° C
- Output 4 pin terminal
- Weight 100 g
- Power Consumption 100 mW
- Dimensions 60×18×18 mm
- Mounting: Desktop, Wall mount
- Package Contents DC voltage monitor, 3m shielded cable (6P6C RJ12), TBW 5-2P



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

VTL100038

SPECIFICATIONS

Operating Temp.	:	Min. -10° C - Max.80° C
Output	:	4 pin terminal
Volt	:	0-15 V
power consumption	:	100 MW
Weight	:	100 g
Dimensioner	:	60 × 18 × 18 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.