

26" ECDIS DNVGL-CG-0339, IACS-E10 Marine approved Panel Monitor, 24VDC, PCAP Touch, 16:10 format

FEATURES

26" DNVGL-CG-0339, IACS-E10, IEC60945 4th marine monitor
350 nits
PCAP touch
Fanless
IP66 on the front
Resolution: 1920 x 1200 - 16:10 format
Active display area: 550 x 344 mm
1 x VGA
1 x HDMI 1.4
1 x DVI-D
Power supply: Terminal block 24VDC
DC input: 9 - 36VDC / 55W typical
Mounting: Panel (Flush) mount with IP66*, VESA100, Bracket mounting
Vibration: 0.7g@DNVGL CG-0339 (Class A)
Shock: 15G, 11ms duration
Optional: Remote control via RS232 D-SUB 9P
DIM: Day Mode, Dusk Mode, Night Mode
Dimensions: 621 x 433 x 86 mm
Cut out dimensions: 596 x 406 mm
Weight: 12.8 kg





Svensk Binär Teknik

MON-MAR26"-T

SPECIFICATIONS

Operating Temp.	:	-15 to 55 deg.C
Montering	:	Panel (Flush) mount with IP66*, VESA, Bracket mounting
Strømforsyning	:	24V DC terminal block
Touch	:	PCAP USB



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.