

WLAN-AP3000AX-U

3000Mbit 2.4/5GHz outdoor Wifi Access Point,
Gateway, Repeater, Wi-Fi Mesh. IP67 aluminum
housing, PoE+ -40 - +70°C

FEATURES

- Outdoor robust Dual Band Access Point etc.
- AP, Gateway, Repeater, Wi-Fi Mesh
- 2.4GHz and 5GHz, 600/2400Mbit (3000Mbit)
- Up to 256 clients Wi-Fi 6
- 1 x RJ45 Gigabit port PoE+
- IEEE 802.11ac 2T2R - Wave 2
- Up to 20dBm (EIRP)
- 4 x N-female connector
- IP67 cast aluminum housing for mast mounting
- Operating temperature: -40 - +70°C
- Real-time Wifi channel analyzer
- Dimensions: 295 x 231 x 80 mm
- Weight: 2.5kg
- Supply: PoE, 48V/0.5A (PoE+)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Operating Temp.	:	-40~ 70 degrees C
Andet	:	Mesh Auto Channel Selection 5-level Transmit Power Control: Max (100%), Efficient (75%), Enhanced (50%), Standard (25%) or Min (15%) Client Limit Control, Coverage Threshold Wi-Fi channel analysis chart Seamless Roaming Beamforming BSS Coloring
Antenne	:	Built-in four N-type connectors
Interface	:	PoE WAN/LAN: 1 x 10/100/1000BASE-T, auto-MDI/MDIX, 802.3at PoE In
IP-Tæthed	:	IP67
Kanaler	:	20MHz, 40MHz, 80MHz, 160MHz
Modes	:	Access Point Gateway Repeater WISP Mesh
PoE	:	48V 0.5A, IEEE 802.3at PoE+, < 15W
Sikkerhed	:	Enable/Disable SSID Broadcast Wireless Max. 32 MAC address filtering User Isolation
VLAN	:	IEEE 802.1Q VLAN (VID: 1~4094) SSID-to-VLAN mapping to up to 4 SSIDs
Dimensioner	:	231 x 80 x 295 mm

