

Wireless Transmitter/Receiver for HDMI / SDI Video signal

FEATURES

3G-SDI and HDMI Inputs and Outputs
Transmitter: 1x USB-C (5 VDC) Input
Receiver: 1x USB-C (5 VDC) Input
Live Streaming via Mobile Device & App
Range 152.4m max (Line-of-Sight)
HDMI/SDI
1080p: 60/59.94/50/30/29.97/25/24/23.98
1080i: 60/50
720p: 60/50
Operating temp. 0 to 50°C
Dimensions: 113 x 65 x 29.2mm





Svensk Binär Teknik

SDI-WIFI150

SPECIFICATIONS

Operating Temp.	:	0 to 50°C
Afstand	:	500' / 152.4 m (Line-of-Sight)
Formater	:	HDMI/SDI 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/50 720p: 60/50
Frekvens	:	5 GHz
Skærm	:	Transmitter: 1,3" OLED, Receiver: 1,3" OLED
Strømforsyning	:	Transmitter: 1 x USB-C (5 VDC) Input Receiver: 1 x USB-C (5 VDC) Input
Dimension	:	113 x 65 x 29.2 mm
Weight	:	200g



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.