

4G SMS alarm with 8 x Digital input, 6 x Analog input,
4 x Relay outputs. Alarms to mobile phone via SMS or
call, APP

FEATURES

8 x digital inputs Dry contact/wet contact (Close:
10~30V; Open: 0~3V)
6 x analog inputs. 12 bit resolution
0-5V, 4-20mA or 0-20mA
4 x relay outputs 5A/30VDC, 5A/250VAC
Up to 10 alarm receivers
1 x USB port for setup
GSM 3G 4G mobile network
9-36VDC (12V/300mA)
Backup battery 3.7V 1200mAh
Operating temperature -10- + 70 °C
Setup via USB cable
Customized SMS alert messages
APP for iOS and Android
Supplied WITHOUT SIM CARD
Power supply included
Magnetic antenna included





SPECIFICATIONS

Digital I/O	:	8x DI Dry Contact/Wet Contact(Close: 10~30V; Open: 0~3V), 6x AI(Differential input, 4-20mA/0-20mA/0-5V), 4xDO(Relay output (5A@30VDC, 5A@250VAC))
USB	:	1xMini USB
Serial	:	1x RS485(Modbus RTU(slave), Modbus RTU(master))
Batteri	:	Backup Battery 3.7V/850mA
IP-Tæthed	:	IP30
Luftfugtighed	:	-45~85°C, 5~95% RH
Montering	:	Wall-mounting or DIN Rail mounting
Netværk	:	4G
Sensor	:	AM2301 -40 to +80°C / 0 to 99RH% (not included!)
Strømforsyning	:	DC 9~36V
Dimensioner	:	108x82x40mm

