

10.1" Rugged ATEX Approved Tablet, IP65, 1920x1080

FEATURES

- 10.1" Rugged ATEX Tablet
- ATEX/IECEX Zone 2 Approved
- Intel® Core™ i5-1235U
- Up to 2TB M.2 NVMe SSD
- Up to 32GB RAM
- 10.1" 1920 x 1200 IPS LED
- 800 Nits
- Optical Bonding
- IP65 Approved
- Windows 10 & 11
- WiFi and BT Support
- WWAN 4G/5G Support (Optional)
- Dimensions 271.5 x 198.2 x 23.3 mm





SPECIFICATIONS

CPU	:	Intel Core i5-1235U (up to 4.4GHz)
USB	:	1 x USB 3.0 (Type A), 1 x USB 3.0 (Type-C support Power Delivery 20V In and ALT mode)
LAN	:	1 x RJ45-10/100/1000 GigaLAN port
Batteri	:	Hot-swappable 11.55V, typ. 4558 mAh Li-Polymer Battery (3S2P)
IP-Tæthed	:	IP65
Levetid	:	Battery operating time: 8 hours
Luftfugtighed	:	10% to 90% RH, Non-Condensing
RFID	:	HF RFID reader 13.56 MHz (Can be purchased)
Slot	:	1 x Micro SDXC slot & 1 x Nano SIM card slot
WiFi/WLAN	:	Supports
Operating Systems	:	Windows 10 IoT Enterprise LTSC (64 bit) or Windows 11 IoT Enterprise LTSC (64 bit)
Dimension	:	271.5 x 198.2 x 23.3 mm





SPECIFICATIONS

Resolution	:	1920x1200
Power Type	:	19V DC, 100-240V, 50-60Hz
Certificate	:	CE, FCC IECEx Class I, Zone 2, Ex ic IIC T4 Gc ATEX Class I, Zone 2, II 3G Ex ic IIC T4 Gc Class I, Division 2, Groups A, B, C, D, T4
RAM	:	8GB DDR5 SDRAM (Up to max. 32GB)
Display	:	Projected Capacitive Multi Touch
Panel size	:	10.1 inches
brightness	:	800.0 nits
WWAN	:	4G LTE (Can be purchased), 5G (Can be purchased)
GNSS	:	GPS, GLONASS
Camera	:	2MP Front, 8MP Rear Camera with auto-focus and LED light
Docking	:	1 x 19-pin docking connector





Svensk Binär Teknik

TABLET10-EX

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.