Svensk Binär Teknik

VPN Security Router with Dual-WAN Load Balancing and 1x SFP, 5x RJ45 Ports

FEATURES

Flexible VPN security solution with fiber capability
Dual-WAN failover and load balancing
4 x 10/100/1000BASE-T RJ45 Ethernet ports
1 x 1000BASE-X SFP slot for WAN interface
1 x USB 3.0 port for system backup and restore
Supports SSL VPN, IPSec, PPTP and L2TP
Stateful Packet Inspection (SPI) firewall
Content filtering for URL blocking
Power requirements: 100-240V AC, 50-60Hz
Max power consumption: 3.7 watts
Metal enclosure, 1U height, dimensions: 330 x 155 x 43.5 mm
Desktop installation or rack mounting options

Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden

042 14 10 85

salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.

SPECIFICATIONS

USB	:	1 USB 3.0 port for system configuration backup and restore
Operating Temp.	:	0 ~ 50 degrees C
AES Kryptering	:	DES, 3DES, AES or AES-128/192/256 encrypting
Forsyning	:	100-240V AC 50/60Hz auto-sensing
Interface	:	Web browser SNMP v1, v2c Smart Discovery utility/UNI-NMS supported
Mål og vægt	:	330 x 155 x 43.5mm / 1.3 kg
Certification	:	CE, FCC

Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden

042 14 10 85

salg@danbit.dk