



Svensk Binär Teknik

BOOST-HDMI100-60-4K6

HDMI Extender 4K60Hz KVM & USB/Audio/RS232/IR Extender - 100 m CAT6 / 60 km Fiber

FEATURES

- Supports resolutions up to 4K@60Hz (4:4:4)
- Transmission up to 100 m via Cat5e/6 or 60 km via fiber (SFP module)
- HDMI loop-out on the transmitter
- 4x USB 2.0 ports on the receiver (KVM functionality)
- Bi-directional analog audio, RS232, and IR control
- Low power consumption, compact design
- Power supply: TX: 5V 2A, RX: 5V 2A
- Operating Temperature: 0-55°C
- Ideal for control rooms, digital signage, and industrial environments.



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

BOOST-HDMI100-60-4K6

SPECIFICATIONS

Input	:	TX: HDMI Type-A, RX: RJ45, SFP
Output	:	TX: RJ45, SFP, RX: HDMI Type-A
Operating Temperature	:	0-55°C
Resolution	:	Max: 4K@60Hz
Power Supply	:	TX: 5V 2A, RX: 5V 2A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.