



Svensk Binär Teknik

BOOST-HDMI100-U-4K6

HDMI Extender 4K60 KVM over Cat6 (100 m) with USB 2.0 & Audio

FEATURES

- Supports video resolution up to 4K@60Hz (4:4:4)
- Extends HDMI, USB 2.0, and audio up to 100 m over Cat6 (HDBaseT)
- 4x USB 2.0 ports on the receiver for remote devices
- Supports Ethernet transmission and CEC pass-through
- Operating Temperature: 0-45°C
- Power Supply: TX: 12V 1.5A, RX: 12V 1.5A
- Perfect for digital signage, control rooms, and industrial AV applications.



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

BOOST-HDMI100-U-4K6

SPECIFICATIONS

Input	:	TX: HDMI, RX: HDBaseT
Output	:	TX: HDBaseT, RX: HDMI
Operating Temperature	:	0-45°C
Resolution	:	Max: 4K@60Hz 4:4:4
Power Supply	:	TX: 12V 1.5A, RX: 12V 1.5A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.