



Svensk Binär Teknik

BOOST-HDMI70-POH-4K6

HDMI Extender 4K60 4:4:4 (70 m) with IR, RS232 & PoH over CAT5e

FEATURES

- Supports True 4K@60Hz (4:4:4) video transmission up to 70 m over CAT5e
- Power over HDBaseT (PoH) - power the system from either TX or RX
- Bi-directional IR & RS232 control for remote management at both ends
- CEC & EDID pass-through for seamless device compatibility
- Extends 4K@60Hz up to 70 m, 1080p even further with higher-grade cabling
- HDMI 2.0 & HDCP 2.2 compliant for modern AV and protected content
- Operating Temperature: 0-55°C
- Power Supply: TX: 12V 1.5A, RX: 12V 1.5A
- Ideal for pro AV & signage.



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

BOOST-HDMI70-POH-4K6

SPECIFICATIONS

Input	:	TX: HDMI, RX: HDBaseT
Output	:	TX: HDBaseT, RX: 2 x HDMI
Operating Temperature	:	0-55°C
Resolution	:	Max: 4K@60Hz 4:4:4
Power Supply	:	TX: 12V 1.5A, RX: 12V 1.5A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.