



Svensk Binär Teknik

HDMI-MATRIX10X10-4K3

10×10 HDMI HDBaseT Matrix Switcher (4K@30Hz, 100 m) with Ethernet, IR & RS-232 FEATURES

10×10 HDMI matrix switching with flexible source-to-display routing.
Supports 4K@30Hz resolution for high-quality UHD video.
Extends HDMI, IR and RS232 signals up to 100 m over CAT5e/CAT6 cabling.
Includes 2 local HDMI loop-outs and 8 HDBaseT outputs for remote displays.
Multiple control options via front panel LCM, IR remote, RS232, Ethernet, Web GUI and mobile app.
Professional AV integration with HDCP, EDID management, 3D video and high-definition audio formats.



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

HDMI-MATRIX10X10-4K3

SPECIFICATIONS

Input	:	8 x HDMI Type A, 2 x HDBaseT
Output	:	2 x HDMI Type A, 8 x HDBaseT
Operating Temperature	:	0-55°C
Resolution	:	Max. 4K@30Hz 4:4:4 12bit
Power Supply	:	5V 2A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.