

HDMI 4K60 KVM over IP Extender with PoE, 100 m Cat / 60 km Fiber, USB / RS232 / IR / Audio

FEATURES

- True 4K@60Hz (4:4:4) video with full-bandwidth HDMI over IP
- Up to 100 m over Cat5e/6 or 60 km over single-mode fiber
- PoE (Power over Ethernet) input (approx. 15W) removes need for separate power supply
- Built-in HDMI loop-out at transmitter for local display monitoring
- USB KVM + RS232 + bi-directional IR and embedded audio support
- Operating Temperature: 0 to 55°C
- Power Supply: TX: DC 12V 1.5A, RX: DC 12V 1.5A
- Compatible with Ethernet switches for scalable distribution, video wall, matrix deployments





Svensk Binär Teknik

BOOST-HDMI150-U-4K

SPECIFICATIONS

Input	:	TX: HDMI, RX: RJ45
Output	:	TX: RJ45, RX: HDMI
Operating Temperature	:	0 to 55°C
Resolution	:	Max: 4K@30Hz 4:4:4
Power Supply	:	TX: DC 12V 1.5A, RX: DC 12V 1.5A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.