

BOOST-HDMI120-UF4K3

HDMI 4K KVM Extender 140 m CAT6 / 120 m CAT5e + Fiber (USB, Audio, RS232, IR)

FEATURES

- 4K@30Hz (4:4:4) video capability
- Transmission distances: 120 m (CAT5e), 140 m (CAT6), 60 km (fiber)
- Local HDMI loop-out on transmitter for nearby display
- 4 USB 2.0 ports at receiver end for remote peripherals
- Bi-directional audio, IR & RS232 control support
- Operating Temperature: 0 to 55°C
- Power Supply: DC 5V 2A
- EDID management & compatibility with IP repeater modules



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

BOOST-HDMI120-UF4K3

SPECIFICATIONS

Input	:	TX:1 x HDMI Type-A, RX: 1 x RJ45, 1 x SFP
Output	:	TX: 1 x RJ45, 1 x SFP, RX: 1 x HDMI Type-A
Operating Temperature	:	0 to 55°C
Resolution	:	Max: 4K@30Hz
Power Supply	:	DC 5V 2A



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.