

AD16S12PCI-LC

Adlink PCI-9111DG. 16 kanalers A/D dataopsamling,
12 bit, 100 kHz, I/O, PCI

FEATURES

- Supporterer 32-bit 5 V PCI bus
- 12-bit A/D resolution (PCI-9111DG)
- 16-CH single-ended analog inputs
- Op til 100 kS/s sampling rate
- On-board 1 k-sample A/D FIFO
- Programmerbar forstærkning på x1, x2, x4, x8, x16
- Bipolar analog input-område



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

AD16S12PCI-LC

SPECIFICATIONS

Digital I/O	:	16 TTL ind- og 16 TTL udgange samt ekstra 4bit programmerbare I/O
Stik	:	DB37 hunstik til analoge ind- og udgange samt til programmerbare digital I/O. 2x20 ben IDC stik til 16 digitale ind- og udgange
Tæller	:	Type 8254 - kan bruges som Timer, Pacer trigger og Pre-trigger tæller



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.