

ESW5G-DT

5 port Gigabit RJ45 switch -40-75° DIN - 9-48VDC,  
24VAC, un-managed switch

## FEATURES

- Unmanaged 5 port 10/100/1000Mbit
- Redundant power input
- 9 - 48VDC
- 24 VAC
- Dimensions: 135 x 88 x 32 mm



Binär Teknik AB  
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



## SPECIFICATIONS

|                          |   |                                                                                  |
|--------------------------|---|----------------------------------------------------------------------------------|
| Buffer                   | : | 128 KB                                                                           |
| Forsyning                | : | Redundant 12 - 48 VDC eller 24 VAC, 5,28 W v. 48 VDC, 8,3 W v. 24 VAC (terminal) |
| Indikatorer og kontakter | : | Spænding, link, aktivitet, fejl, hastighed                                       |
| Miljø                    | : | Driftstemperatur -40 til +75° C                                                  |
| Montering                | : | DIN-skinne                                                                       |
| Porte                    | : | 5 x RJ45 porte, 10/100/1000 Mbit, automatisk detektering af lige/krydset kabel   |
| Mål                      | : | 135 x 88 x 32 mm                                                                 |

