

1 port serial port server RS232, POE or 12-48VDC. Serial Device Server

FEATURES

- External COM port via Ethernet and Internet
- RS232 Serialport via DB9 male
- Power supplied from PoE
- can be powered from 12 - 48VDC / 1.7 watts
- Short Power Jack Pigtail Cable included
- Purchase Power supply, not included
- 1 x RJ45 with PoE input
- DIN mount
- Operating temperature: -25 - + 75 ° C
- Dim: 90 x 52 x 27 mm





SPECIFICATIONS

Administration	:	Indstilles over netværk via http
Operating Temp.	:	-25 - 75°C
Andet	:	
Kabinet	:	Flammehæmmet plastic hus, der overholder UL94-V0 standarden
Montering	:	DIN skinne
Netværk	:	1 x 10/100 Mbit Ethernet netværksport
Porte	:	Hastigheder fra 300 bit/s til 115,2 Kbit/s. Databit: 5/6/7/8. Stopbit:1/2. Paritet: Lige/Ulige/Ingen
Protokol	:	TCP, UDP, DHCP, HTTP
Signaler	:	TxD, RxD, RTS,CTS, GND
Software	:	COM-driver til Windows XP, Vista 32/64 bit Windows 7 32/64 bit og 2003 server 32/64 bit og 2008 server 32/64 bit samt WIN8/10
Stik	:	Seriell port: DB9 hanstik. Ethernet: 1x RJ45 hunstik
Strømforsyning	:	12 ~ 48 VDC via DC Jack eller 48 VDC via netværkskabel. Maks 1,2W





Svensk Binär Teknik

ETH1SER-POE-I

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.