

Ports 2 MODBUS serielportserver 1 x RS232 + 1 x RS422 / 485th Serial Device Server Box Box option FEATURES

Modbus over the Ethernet or Internet
MODBUS server with 1 x RS232 and 1 x 422/485
Can run Device to Device
0/100 Mbps Ethernet port, auto MDI / MDIX, 10/100 auto, 1500V magnetic insulation only on
RS485 RS232 Modbus ASCII / RTU port, 1 RS422 / 485 Modbus ASCII / RTU port, 16V / 400W TVS isolated, RS485 automatic line control
9 ~ 30VDC power input, IP30 enclosure , DIN rail mounting structure, USB port (Modbus serial port expansion and capture of memory)





SPECIFICATIONS

USB	:	2 stk. USB 2.0 porte. Bruges til udvidelse, samt gemme/hente opsætningen via en USB nøgle
Administration	:	Web interface
Operating Temp.	:	-40 – 85 °C
Kabinet	:	IP30-tæt metalkabinet i format 49 x 130 x 105 mm (H x B x D)
Montering	:	DIN skinne
Netværk	:	1 x 10/100 Mbit kablet Ethernet netværksport.
Porte	:	1 x RS232 port og 1 x RS422/485 port. Hastigheder fra 150 bit/s til 921 Kbit/s, Databit:5/6/7/8, Stopbit:1/2. Paritet: Lige/Ulige/Ingen
Protokol	:	TCP/broadcast TCP/server, TCP/klient, UDP/server, UDP/Klient, Modbus/ASCII, Modbus/RTU og Master/Slave
Signaler	:	RS232: TxD, RxD, RTS,CTS, DTR, DSR, DCD, GND. RS422: TxD+, TxD-, RxD+, RxD-, GND. RS485 2-leder: Data+, Data-, GND
Stik	:	RS232 port: DB9 han. RS422/485 port: terminalblok. Ethernet: 1 x RJ45 hunstik
Strømforsyning	:	9 ~ 30 VDC via terminalblok; forbrug ca. 10 watt afhængigt af tilsluttet ekstra udstyr via USB bussen

