

2 x RS232, RS422 eller RS485 seriella portar för PCI,
2 x DB9 hane

FEATURES

- 2 x rs232 / 422/485 portar
- PCI version 2.1 (32bit) - 3.3 / 5.0V
- RS232: TX, RX, CTS, RTS - Optisk ISO
- RS422: TXD +/-, RXD + / -, RTS, CTS, GND
- RS485: Data + / Data, GND
- 2 x dB9 Han
- Upp till 921.6kbps
- Inbyggd uppsägning: 120 ohm
- Dos, Windows 98, NT, 2000, XP, Win7, Win8, 2003, Linux





SPECIFICATIONS

Baudrate	:	Maks. 921,6 Kbit/s
Drivere	:	DOS, Windows 98, NT, 2000, XP, Win7, Win8, 2003 og Linux
Duplex	:	Point-to-point fuld duplex eller multidrop halv duplex
FIFO	:	16 bytes
I/O	:	Plug and Play
PCI	:	3,3 og 5 V
Porte	:	2 x RS232/422/485
Profil	:	Kan kun leveres med høj profil
Signaler	:	RS-422: TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND(4-tråds) RS-485: Data+/-, GND (2-tråds)
Stik	:	2 x DB9 han
Terminering	:	Ingen terminering nødvendig; Termineringsmodstande (120 Ω) er indbygget
UART	:	16C550

