

2 portar seriell portserver, 2 x RS232 / 422/485, LAN och WiFi. Serial Device Server över Ethernet. 9 - 48VDC.

FEATURES

Extern COM-portar via Ethernet och Internet
Serial Device Server till RS232/422/485
LAN och WiFi





SPECIFICATIONS

Administration	:	Indstilles over netværk via http, Telnet konsol eller Windowsprogram
Driftstemperatur	:	-10 - 60 °C
Kabinet	:	IP50-tæt metalkabinet i format 47 x 110 x 90 mm (H x B x D)
Montering	:	DIN skinne
Porte	:	To serielle porte, der kan bruges frit som RS232, RS422 eller RS485. Hastigheder fra 110 bit/s til 921 Kbit/s, Databit:5/6/7/8, Stopbit:1/2. Paritet: Lige/Ulige/Ingen
Protokol	:	Pv4, ICMP, TCP, UDP, DHCP Klient, SNMP, SMTP, HTTP, DNS, NTP, RADIUS, RFC2217, WPS
Signaler	:	RS232: TxD, RxD, RTS,CTS, DTR, DSR, DCD, GND. RS422: TxD+, TxD-, RxD+, RxD-, GND. RS485 2-leder: Data+, Data-, GND. RS485 4-leder: TxD+, TxD-, RxD+, RxD-, GND
Software	:	COM driver til Windows XP, 2003, Win 7 32/64 bit og Win 8
Stik	:	Serielle porte: 2 x DB9 han. Ethernet: 1 x RJ45 hunstik og 1 x R/SMA stik til medfølgende antenne
Strømforsyning	:	9 ~ 48 VDC via terminalblok (forbrug under transmission ca. 5,85 watt). Leveres uden strømforsyning benyt DC24V625MA-D

