

12" Panelmonitor, Touch, IP65 front, VGA, DVI-D, HDMI, 500nits, 4:3 format USB (standard) eller RS232 touch

FEATURES

- 12" LCD-skärm
- IP65 tätad NEMA 4/12 fram
- DVI, HDMI, VGA
- Upplösning 1024 x 768 - 4:3
- Pekskärm RS232 eller USB-gränssnitt (standard med USB)
- Vesa 100 fäste, Panelmontering.
- OSD
- 12/24Vdc standardskruvterminal
- Frivillig! Rackmontering
- Frivillig! 230 vak





SPECIFICATIONS

Driftstemperatur	:	0°C ~ +55°C
Approval	:	CE
Forsyning	:	15 W Screw-type external AC / DC power adapter
Lysstyrke	:	500 nits
Montering	:	Vesa 100, Panel mount, Option: Rackmount, Desktop stand, wall mount
Tilbehør	:	1 x VGA cable 1 x RS232 or USB cable for touchscreen (for touch version) 1 x Audio cable 1 x EU/US power cord (for AC version)
Touch	:	Resistive touchscreen
Vikt	:	2,35kg
Dimensioner	:	(W x D x H) 311.81 x 54.95 x 250.31 mm (12.28" x 2.16" x 9.85")

