

SER8PCI-K+

8 x RS232 seriella portar för PCI - Korenix JetCard1208L

FEATURES

ÅTERSTÄLLNING REA
Seriekort JetCard1208L
PCI - Lågt oh högt bakplan
8 x RS232
Upp till Win 7 (32bit)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Baudrate	:	50 bit/s ~ 921,6 Kbit/s
Buffer	:	128 bytes FIFO
Drivere	:	Windows 2000, XP, Win7 32 bit og 2003
Høj/lav profil	:	Høj bagplade (ikke lavprofil)
I/O	:	PnP, vælges af BIOS
Isolation	:	15 KV ESD beskyttelse
Paritet	:	None, Even, Odd, Space eller Mark
Porte	:	8 porte til RS232. Op til 4 kort kan monteres i samme system (giver maks. 32 porte i alt)
Signaler	:	TxD, RxD, RTS, CTS, DTR, DSR, DCD og GND
Spænding	:	3.3 og 5 V PCI
Stik	:	1x DB62 hunstik(100 cm kabel med 1 x DB37 hhv. DB62 hanstik og 4/8 x DB9 hanstik medfølger)
Strømforbrug	:	Maks. 120 mA (+5 V)





Svensk Binär Teknik

SER8PCI-K+

SPECIFICATIONS

UART : 16C950 kompatibel



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.