

1 x USB till RS232 / RS422 / RS485 adapter, optiskt isolerade

FEATURES

- Få en RS485 eller RS422 eller RS232-port på PC'n via USB-porten
- Galvanisk isolering (optisk) 2 kV
- DB9 hane och skruv terminal till 232/422/485 anslutning
- Terminiering och jumpere
- baudhastigheten 300bit / s två 921,6 kbit / s
- Välj mellan RS232, RS422 och RS485 med DIP switch
- Stöder Win7/8/10 samt Mac och Linux
- Drift Temp . 0 ° till 55 ° C,





SPECIFICATIONS

USB	:	USB 2.0 High Speed, USB 1.1 compliant Speed 480Mbps, hi-speed USB
Driftstemperatur	:	0°C to 55°C (32°F to 131°F)
Approval	:	CE, FCC
Baudrate	:	Data Bits 7, 8 Parity None, Even, Odd, Mark, Space Stop Bit 1, 2 Flow Control Hardware (RTS, CTS), XON/XOFF
Isolation	:	25kV ESD protection for all signals 2000V DC optical isolation for all signals
Kabel	:	0,9 m
Kabel	:	USB kabel medfølger
Luftfugtighed	:	5% to 95% RH
Montering	:	DIN rail bracket
OS SUPPORT	:	Windows 2000 up to Windows 10 Windows Server 2000 up to 2018 Linux kernel 2.6+ Mac OS X support available
Porte	:	Max. Speed RS-232:up to 1Mbps RS-422/485:up to 3Mbps RS-232 Signals RxD, TxD, GND, RTS, CTS RS-422 Signals TxD-, TxD+, RxD+, RxD-, GND, RTS-, RTS+, CTS+, CTS- RS-485 Signals (4 wire) TxD-, TxD+, RxD+, RxD-, GND RS-485 Signals (2 wire) Data-, Data+, GND
Signaler	:	RS422/RS485





Svensk Binär Teknik

CNV-USB-UNI-I

SPECIFICATIONS

Strømforsyning	:	Power Input Power supplied via USB connector No external power needed Power Output 5V, 150mA through pin 5 of terminal block
Temperatur	:	-20°C to 75°C (-4°F to 167°F)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.