

DI32O32PCI

ADLINK LPCI-7200. 32 kanalers D/I og D/O kort, 12MB/s, PCI

FEATURES

- Support a 32-bit 3.3 V or 5 V PCI bus
- 32-CH TTL digital inputs and 32-CH TTL digital outputs
- Up to 12 MB/s transfer rate
- Bus mastering DMA for both digital inputs and outputs
- On-board programmable timer pacer clock
- Supports handshaking digital I/O transfer mode
- Multiple programmable interrupt sources
- Compact, low-profile PCI size PCB



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

DI32032PCI

SPECIFICATIONS

Indgang	:	32 TTL indgange med indbygget FIFO. Understøtter DMA Overfører op til 12 MB pr. sekund
Software	:	Driver til Windows 2000, XP, Win7 og Win8 Labview og Linux medfølger
Stik	:	2 x DB37 hun fordelt på 2 bagplader
Udgange	:	32 TTL udgange
Dimensioner	:	98 x 173 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.