



ETH1SER485POE-I

1 port RS485 / 422 seriell portserver. Seriell
enhetsserver med RS422 eller RS485 kan levereras
med PoE

FEATURES

- 1-portars RS-422/485 till Ethernet-enhetsserver
- 1x 10/100 Mbit/s RJ45 LAN
- DB9-hankontakt **eller** 5-polig seriell kontakt för kopplingsplint
- Baudrater: 300 till 115,2 kbps
- Konfigurerbar: 6/7/8 databitar, 1/2 stoppbitar, paritet Ingen/Udda/Jämn
- Inbyggd övervakningsfunktion för pålitlig drift dygnet runt
- Bred strömingång: 7-40 VDC (DC-uttag) / PoE (48 VDC via Ethernet)
- Industriell metallkapsling, ~300 g
- Driftstemperatur 0-55 °C; luftfuktighet 5-95 % RF
- IS-modellen har 2,5 kVrms-isolering och 500 W överspänningsskydd



SPECIFICATIONS

Serial	:	Ports: 1 × RS422/RS485 / RS422 signals: TXD+, TXD−, RXD+, RXD−, GND / RS485 signals: DATA+ (A), DATA− (B), GND
Driftstemperatur	:	Operating temperature: 0 to 55 °C
Baudrate	:	300 bps to 115.2 kbps
Forsyning	:	7-40 VDC via DC jack / 48 VDC via Ethernet cable (PoE model only)
Isolation	:	Isolation: 2500 Vrms / Surge protection: 500 W
Netværk	:	1x RJ45 10/100 Mbps (auto-negotiation)
Porte	:	Serial: DB9 male (RS422/485) or 5-pin terminal block
Watchdog	:	Watchdog timer: Built-in

