



Svensk Binär Teknik

IPC-I5-2PCIEX

Industriell BOX PC med 2 x PCIe expansion. Intel i7 /
i5 / i3 Haswell

FEATURES

- fläktlös design
- Wide Range likströmsingång (9 ~ 36V)
- iAMT stöds
- Trippel oberoende displayer (DVI-I + Display * 2) stöds
- Valfri WiFi eller HSUPA trådlös anslutning stöds
- Robust Design för Shock / vibrationsskydd
- Minnesstöd upp till 16 GB (DDR3)
- RAID 0,1 stöds



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

CPU	:	4th Generation Intel® Core™ i7/i5/i3 or Haswell Processor in LGA1150 socket
Chipset	:	Intel® Q87
USB	:	6 x USB 3.0/ 2.0 ports Internal USB dongle (Optional)
Driftstemperatur	:	-20 ~ 55°C (-4 ~ 131°F), ambient w/ air flow
Chok/Vibration	:	Vibration 3 Grms/5~500Hz/random operation w/ SSD Shock Operating 40G (11ms), Non-operating 60G with SSD
Forsyning	:	DC 9~36V input w/ 4-pin terminal block
Grafik	:	Integrated Intel® HD 4600 2 x DisplayPort female connector for Digital Video output 1 x DVI-I female connector for Digital/Analog Video output
Hukommelse	:	2 x 204-pin DDR3 SO-DIMM sockets, supporting 1600MHz SDRAM up to 16GB
I/O	:	1 x DB25 connector for 1 x DIO (8 in/8 out) port or 1 x LPT port (either one) DIO by default, can be changed to LPT
Ledige Slots	:	1 x PCIe x 16 slot 1 x PCIe x8 slot (via x 4 lanes)
Luftfugtighed	:	10 ~ 95% @ 55°C (non-condensing)
Materiale	:	Aluminum alloy





SPECIFICATIONS

Netværk	:	3 x RJ45, 1 x Intel® i217LM GbE PHY w/ iAMT 2 x Intel® i210IT GbE
OS SUPPORT	:	W7 Pro / WS7E / WE8 STD
Porte	:	COM1/ COM2 RS-232/422/485 Selectable COM3/COM4 RS-232
SATA	:	2 x Serial ATA ports with RAID 0/1 support
Strømforbrug	:	Max.75W(w/o I/O Card)
Watchdog	:	1~255 levels reset
Vikt	:	7 kg (15.43 lb)
Dimensioner	:	225 x 267 x 120 mm

