

10.4" Panel PC godkänd till användning i tåg, (EN 50155 for railway)

FEATURES

- Sunlight readable 10.4"
- 1000 Nits
- Auto-dimming
- 25°C to +70°C
- EN 50155 certified for railway





SPECIFICATIONS

Chipset	:	SoC Integrated
USB	:	2 x USB 2.0 (M12, A-coded)
Driftstemperatur	:	-25°C ~ +70°C (-13°F ~ +158°F)
Övrig	:	1 x isolated CAN bus 1 x isolated DIO (6-IN/2OUT) (phoenix type) 1 x isolated DC for power input (M12, A-coded)
Approval	:	EN 50155, EN 50121-3-2 EMC, EN 61373 (Shock/Vibration), EN 45545 (fire) certified Compliance with UIC 612-01 (keypad)
Ethernet	:	2 x isolated 10/100/1000Mbps (M12, X-coded)
Forsyning	:	16.8V to 30V DC or 77V to 137.5 VDC 10ms hold up time (S2) Power Comsumpt
Hukommelse	:	DDR3 4 GB (default) or 8 GB memory onboard
IP-Tæthed	:	Front Bezel IP65, NEMA 4 rugged protection, aluminum front bezel
Lyd	:	Line out/Line in/speaker out
Montering	:	Suspension mount VESA mount
Msata	:	1 x mSATA





SPECIFICATIONS

Porte	:	2 x isolated RS-232/422/485 (M12, A-coded)
Skærm	:	10.4" SVGA TFT LCD 1000 nits 800 x 600 pixels
Touch	:	5-wire resistive touch panel
Udvidelser	:	2 x PCI Express Mini Card
Watchdog	:	255 levels, 1 ~ 255 sec.
Vikt	:	2.4 kg (5.29 lb) / 5 kg (11.02 lb)
Dimensioner	:	310 x 65.05 x 216 mm (12.20" x 2.56" x 8.50")

