

Ethernet till CAN-enhets server. CAN till Ethernet Gateway. Med 1 x CAN, RS232 och RS485. FEATURES

Internetkommunikationskontroll med 1 x CAN-buss,
1 x RS-232, 1 x RS-485 och 1 x Ethernet
10/100 Base-TX Ethernet Controller
TCP / IP Protokoll
80 MHz CPU
1 X RS-232 Port, 1 x RS-485 Port och 1X CAN-port
kan användas samtidigt
Max Transmissionshastighet upp till 1 M BPS för
CAN och 115.2Kbps för RS-232 RS-485
7 -Segment LED-display
Software Configuration för CAN och RS-232
Webkonfiguration
Upp till 25 Ethernet Client Connections
Stödjer Virtual Com



SPECIFICATIONS

Driftstemperatur	:	-25 ~ 75 °C
Controller	:	10/100Base-TX Ethernet Controller (Auto-negotiating, Auto_MDIX) Connector RJ-45 with LED indicator
Forsyning	:	Power supply Unregulated +10 ~ +30 VDC Protection Power reverse polarity protection, Over-voltage brown-out protection Power Consumption 2.5 W
Isolation	:	1000 VDC for DC-to-DC, 2500 Vrms for photo-couple
Montering	:	DIN-Rail
Stik	:	CAN BUS: 2-pin screwed terminal block. COM 1 Connector 5-pin screwed terminal block (TxD, RxD, RTS, CTS, GND). COM 2 Connector 2-pin screwed terminal block (DATA+, DATA-)
Dimensioner	:	(W x L x H) 72mm x 122mm x 33mm

