

ESW4SFP2

4 portar 10/100 / 1000mbit RJ45 + 2 portar 100 / 1000Mbit SFP-kortplats, managed switch, 12 - 48VDC och 24VAC

FEATURES

- Snabb Ring, Redundant Ring of kritisk nätverk
- IEEE 1588 Time Protocol, stöder MEF service och synkron Ethernet
- Stöder Modbus TCP-protokollet
- Stöder IGMP snooping till 4 x 10/100 / 1000Mbps RJ45-portar
- 2 x 100 / 1000Mbit SFP-portar
- 12 - 48VDC, är överflödig ingång
- 24 VAC matningsspänning också möjligt
- IP30 metallkapsling med DIN fäste
- temperaturområde från -40 till + 75 ° C





ESW4SFP2

SPECIFICATIONS

Driftstemperatur	:	-40 - 75°
Forsyning	:	Dual 12~48V DC 24V AC
Materiale	:	IP30 metal case
Montering	:	DIN rail kit and wall-mount kit
Porte	:	4 10/100/1000BASE-T RJ45 auto-MDI/MDI-X ports
Slot	:	2 1000BASE-SX/LX/BX SFP interfaces (Port-5 to Port-6) Compatible with 100BASE-FX SFP
Stik	:	Removable 6-pin terminal block for power input Pin 1/2 for Power 1, Pin 3/4 for fault alarm, Pin 5/6 for Power 2
VLAN	:	802.1Q tagged based VLAN, up to 255 VLAN groups Q-in-Q tunneling Private VLAN Edge (PVE) MAC-based VLAN Protocol-based VLAN Voice VLAN MVR (Multicast VLAN Registration) Up to 255 VLAN groups, out of 4094 VLAN IDs
Dimensioner	:	32 x 87x 135 mm

