

ANR-LNX-0601G-SFP

5 portar Industriell 10/100 / 1000Mbit + 1 x 100 /
1000Mbit SFP-kortbrytare, DIN-montering, -10 - + 70
° C, 12 - 48VDC

FEATURES

- 5 x 10/100 / 1000 Mbps Ethernet-portar + 1 x 100 / 1000Mbps SFP-kortplats
- Auto MDI / MDI-X Funktion
- Store-and-Forward Switching Architecture
- 10Gbps Backplane Tyg)
- 8K MAC-adresstabel
- 9.6Kbytes Jumbo ramstöd
- Överspänningsskydd: 3kV
- ESD-skydd: 6kV
- Redundant ströminmatningsdesign - 12 ~ 48VDC
- 1 Reläutgång till port Break Alarm
- IP30 Aluminiumsskåp
- DIN-Rail och Väggmontering
- Temperaturområde: -10 ° till 70 ° C



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



Svensk Binär Teknik

ANR-LNX-0601G-SFP

SPECIFICATIONS

Driftstemperatur	:	-10 - +60
Fiber	:	1 x 100/1000Mbps SFP slot
Forsyning	:	12 -48VDC, redundant
Kabinet	:	Metal, IP30, DIN-beslag, option vægbeslag
Maks. effekt	:	6,9 Watt
Netværk	:	5 x RJ45 10/100/1000Mbps



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.