

ANR-LNX-1802G

16 ports Industriel 10/100Mbit + 2 x 10/100/1000Mbit SFP slot switch, DIN-beslag, -10 - +70°C, 12 - 48VDC FEATURES

- 16 ports 10/100Mbit + 2 ports 10/100/1000Mbit/mini-GBIC Combo
- 7.2 Gbps Back-Plane (Switching Fabric)
- Store-and-Forward Switching Architecture
- 1 Mbits Packet Buffer
- 8K MAC Address Table
- Wide-Range Redundant Power Design 12 - 48VDC
- Transientbeskyttelse 3.000 VDC på Power Line
- 6.000 VDC Ethernet ESD Protection
- IP30 rpbust aluminum kabinet
- DIN-Rail eller Panel monterbar



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



ANR-LNX-1802G

SPECIFICATIONS

Driftstemperatur	:	-10 - +70
Fiber	:	2 x 100/1000Mbps SFP slot
Kabinet	:	Metal, IP30, DIN-beslag,
Maks. effekt	:	9 Watt
Netværk	:	16 x RJ45, 10/100Mbps
Dimensioner	:	72 x 152 x 105mm

