

Embedded Fanless Industry PC Intel Core i3, i5, i7, 3XETHERNET, VGA, DVI, 6X USB

FEATURES

- Intel® Core™ 6th Gen
- Stöd i3, i5, i7 - CPU ingår inte i priset
- Integrerad Intel® HD 530/510 Controller
- Upp till 16 GB DDR4-2133 - Ram ingår ej i Pris
- 3xGbit (1x Intel i219-lm, 2xintel i210-it)
- 4 x USB 3.0
- 2 x USB 2.0
- 2 x RS-232 2x Rs 232/422/485
- VGA DVI
- 8 ~ 35VDC
- Exkl. OS och strömförsörjning
- 25 ° C ~ 70 ° C (kräver speciell SSD och RAM)
- DIN-Rail Mount Kit (tillval)
- 120W AC / DC nätadapter (Optional)
- 8- CH Isolerad DI och 8-CH Isoled DO (Optional)





SPECIFICATIONS

CPU	:	Supports Intel 6th-Gen Core
Chipset	:	Intel® H110 platform controller hub
USB	:	2x USB 2.0 & 4x USB 3.0
Driftstemperatur	:	-25°C ~ 70°C */**
Chok/Vibration	:	Operating, 50 Grms, half-sine 11 ms duration / Operating, 5 Grms, 5-500 Hz, 3 Axes
Ethernet	:	1xGbit Intel I219-LM, 2 x Gbit Intel I210-IT
Forsyning	:	8~35Vdc
Hukommelse	:	MAX. 16GB DDR4-2133 (single SO-DIMM) not included
Input	:	1x 3-pin pluggable terminal block for 8~35 VDC power input
Montering	:	Standard wall mount
Msata	:	1x full-size mSATA socket
Vikt	:	2.8 kg (incl. CPU, memory and HDD)





Svensk Binär Teknik

IPC-I6X-3XGBE

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.