



UPS-3KVA

3 kVA / 2,4 kW UPS med LCD-skärm. 19" Rack / Tower. Sann sinuskurva, inkl. batterilåda för 6 st. 12V/55Ah. 10 timmar v/200W

FEATURES

- Toppklass 3,0 kVA / 2,4 kW online UPS / nödkraft
- Ingång: 110-300 VAC 40Hz-70 Hz
- Utgångsspänning: 230 VAC / 50Hz
- LCD-skärm
- Enfas
- Genuine Sine Curves - ger mindre ljud på utspänningen
- Rack / Tower 2 i 1
- Inbyggd ingång OVCD
- Fot / ställ eller för montering av rack
- 1 x IEC 320 C20 Terminal (ingång)
- 4 x IEC 320 C13 (utgång)
- Godkännanden: IEC 62040-1 (säkerhet) IEC-62040-2 (EMC)
- Inkl. batteripaket: 6 x 12V / 55Ah





SPECIFICATIONS

Driftstemperatur	:	0-40°C
Alarm	:	Battery Mode Sounding every 4 seconds Low Battery Sounding every second Overload Sounding twice every second Fault Continously sounding
Övrig	:	Optional SNMP Power management from SNMP manager and web browser
Batteri	:	6 x 12V/55Ah
Input	:	110-300 VAC 40Hz ~ 70 Hz
Interface	:	Interface to pc via Smart RS-232 / USB
Kapacitet	:	3.0 kVA / 2,4 kW
LED	:	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators
Montering	:	stander or 19" rack
OS SUPPORT	:	Windows 2000/2003/XP/Vista/2008/7, Linux, Unix, and MAC
Output	:	230 VAC
Software	:	Included





Svensk Binär Teknik

UPS-3KVA

SPECIFICATIONS

Standarder	:	IEC 62040-1 (safety) & IEC-62040-2 (EMC)
Stik	:	1 x IEC 320 C20 Terminal (input) 4 x IEC 320 C13 (output)
Støj	:	Less than 50dBa by 1 Meter
Vikt	:	10 kg without batterypack
Dimensioner	:	480 (D) x 438 (W) x 88 (H) (2U) without batterypack



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.