

10.4" Panel pc 1.6GHz 2xLAN 2xRS232 4xUSB  
Touch IP65 front

## FEATURES

- 10.4 "XGA / SVGA TFT LCD-skärm med LED-bakgrundsbelysning
- Resistiv touch
- Intel® Celeron® Processor N3060 Upp till 2,48 GHz
- 2 Gigabit Lan
- Audio Line Out
- 1 x 204 -Pin så-DIMM DDR3L-1600 MHz, upp till 8 GB
- 2 com ports 1 x RS-232, 1 x RS-232 / 422/485
- 2 x USB 2.0
- 2 x USB 3.0
- IP65 Front
- 24vdc (Option ! 100 till 240Vac)



## SPECIFICATIONS

CPU	:	Intel® Celeron® processor N3060 (up to 2.48 GHz)
Övrig	:	1 x HDMI output
BIOS	:	AMI
Chok/Vibration	:	2G, 5~500Hz, random for SSD
Dimensioner	:	(W x D x H) 292.5 x 45.8 x 235.8 mm (11.52" x 1.80" x 9.28") (W x D x H) 292.5 x 45.8 x 235.8 mm (11.52" x 1.80" x 9.28")
Driftstemperatur	:	Operating Temperature 0°C ~ +50°C (+32°F ~ +122°F) (with W.T. DRAM/HDD in airflow condition) 0°C ~ +45°C (+32°F ~ +113°F) (with W.T. DRAM/HDD)
Ethernet	:	2 x 10/100/1000 Mbps (Intel® i211AT)
Forsyning	:	DC version: 24 VDC with over current protection fuse (option! AC version: 100~240V AC-DC 60W power adapter need to order special)
Hukommelse	:	1 x 204-pin SO-DIMM DDR3L-1600 MHz, up to 8 GB
IP-Tæthed	:	IP65, NEMA 4 rugged protection, plastic front bezel
LCD	:	10.4" XGA/SVGA TFT LCD with LED backlight 350 nits (XGA) 400 nits (SVGA) 1024 x 768 (XGA) 800 x 600 (SVGA)
Lyd	:	Line-out



## SPECIFICATIONS

Porte	:	1 x RS-232 1 x RS-232/422/485
Touch	:	Resistive Type
Udvidelser	:	1 x Full-size PCI Express Mini Card with mSATA 1 x Full-size PCI Express Mini Card with SIM slot
Vikt	:	(net/gross) 1.8 kg (3.96 lb)/3 kg (6.61 lb)
Watchdog	:	255 levels, 0~255 sec.