

8-tums LCD-skärm, beröring med LED-bakljus, IP55 nära framsida, 800nits, läsbara i solljus, -20°C till +60°C, 4:3-format

FEATURES

- 8" TFT LCD-skärm, lämplig för fordon
- Resistive Touch (USB)
- LED-bakgrundsbelysning
- 800 x 600 pixlar (SVGA)
- Ljusstyrka: 800 cd/m² (800nits)
- Läsbar i solljus
- Kontrast 500: 1
- 1 x SD / MMC / MS-kortläsare, 1 x USB A, 1 x Mikrofon
- 1 DVI-anslutning (VGA, 1 x USB och 1 x 12VDC)
- Tillförsel 9-36VDC, 15W
- Driftstemperatur -20 till 60°C
- IP55 Front
- VESA 75, Panel Power. väggmontering
- Mått: 207mm x 173mm x 36.7mm (B x H x D)





SPECIFICATIONS

Driftstemperatur	:	-20°C to 60°
Övrig	:	2 x Built-in speakers (1.2W)
Chok/Vibration	:	Vibration (random): 2.5g@5 ~ 500 Hz □ Vibration Operating: MIL-STD-810G, 514.6 Procedure 1, Category 4, Ground Vehicle – Highway Truck Storage: MIL-STD-810G, 514.6 Procedure 1, Category 4, Integrity Test □ Shock
Interface	:	Lateral: 1 x SD/MMC/MS card reader, 1 x USB type A Host, 1 x Line-out 1 x Mic-in Interface Bottom: 1 x Mic-out, 1 x Line-in, 1 x DVI-D Connector (integrating VGA, USB x 1 and 12VDC x 1)
IP-Tæthed	:	Front panel IP55
Kontrast	:	Contrast ratio: 500 : 1 (typical)
Lysfølsomhed	:	Sunlight-Readable Display with High Brightness LCD (800 cd/m2)
Materiale	:	Enclosure: Plastic PC + ABS
Montering	:	VESA 75, panel and wall mounting
Pixels	:	
Skærm	:	8" SVGA TFT LCD Monitor
Touch	:	4-wire resistant touch Anti-glare coating surface Transmission rate: 82 ± 3%





Svensk Binär Teknik

MON8-TFT-S

SPECIFICATIONS

Dimensioner : 207mm (W) x 173mm (H) x 36.7mm (D)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.