



Svensk Binär Teknik

SW-BPASS6

haneuel bypass-switch, 6 x IEC C13, 1 x IEC C19, FEATURES

Bypass-Switch til udskiftning eller vedligeholdelse af uafbrydelige strømforsyninger (UPS)
19" rackmontering, 1U
Synlig LED-Display
1 output „zur USV“ IEC C13, 10A / IEC C19, 16A
1 input „von USV“ IEC C14, 10A / IEC C20, 16A
4 x IEC C13 udgange 14A
3 x RJ45, LAN og Sensor
1 x IEC C14 10A/ IEC C20 16A Strømforsyning



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



Svensk Binär Teknik

SW-BPASS6

SPECIFICATIONS

Driftstemperatur	:	0-50 °C
Dimensioner	:	43.4 x 4.4 x 16.5 cm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.