

Industriell fläktlös Mini PC, DIN-fäste, Pentium®
N4200 1,1 / 2,5 Ghz Quad core, 3 x Gigabit LAN (2 x
PoE + Typ 2), 8 ~ 35 VDC

FEATURES

- Intel® Apollo Lake Pentium® N4200 fyrkärnig processor
- 3x Gigabit Ethernet-portar från Intel® I210 GbE (2 x PoE + typ 2)
- 1x Programvaruprog. RS232 / 422/485 (COM1)
- 1x RS-422/485-port (COM2) eller tillval: 3x 3-tråds RS-232-portar
- 2x USB3.1 Gen.1
- 2x USB2.0
- 1x DVI-I
- 1x Mini-PCIe i full storlek (USIM-socket)
- 1x mSATA halvstorlek (lagring)
- Alternativ: 2½" SSD / HDD-fäste
- DIN-skena standard (alternativ för väggmontering)
- 25 °C till 70 °C
- 5,6 x 15 x 11 cm



SPECIFICATIONS

CPU	:	N4200 Quad Core 1.6/2.0 GHz
USB	:	2x USB 3.0 2x USB 2.0
Driftstemperatur	:	-25°C ~ 70°C med SSD, -10°C ~ 50°C med HDD
Approval	:	CE/FCC Class A, according to EN 55022, EN55032 & EN 55024
Chok/Vibration	:	Vibration Operating, 5 Grms, 5-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-64) Shock Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
Ethernet	:	3x Gbit by intel I210 GBE controller (2 support POE+ Type2)
Forsyning	:	1x 3-pin pluggable terminal block for 8~35VDC DC input
Grafik	:	Integrated Intel® HD Graphics 505
Hukommelse	:	1x DDR3L-1866, op till 8GB
Luftfugtighed	:	10%~90% , non-condensing
Lyd	:	1x speaker-out, 1x microphone-in
PoE	:	IEEE 802.3at PoE+ on port #2 and #3





Svensk Binär Teknik

EPC-N4200-DIN+POE

SPECIFICATIONS

Porte	:	1x Software-programmable RS-232/422/485 ports (COM1), 3x 3-wire RS-232 ports (COM2/3/4) or 1x RS-422/485 port (COM2)
SATA	:	1x half-size mSATA port, 1x SATA port till 2.5" SSD/ HDD
Vikt	:	0.96Kg
Dimensioner	:	56 x 108 x 153 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.