

MON15-T-HB

15,6" TFT-panelmonitor 1000nits, 10-punkts PCAP
Touch, IP65 front, HDMI, VGA, Composite Video, 16:9
format

FEATURES

- 15,6" TFT LCD
- 16:9-format, 160° / 160° (H/V)
- 10 Point Capacitive Touch, (kan levereras utan beröring)
- 1000 Nits ljusstyrka lämplig i starkt ljus
- 4k30p, 1920x1080 upplösning
- 1 x HDMI 1.4b (2150p, 24/25/30, 1080p 24/25/30/50/60)
- 1 x VGA-ingång
- 1 x AV-ingång
- Ljud 3,5 mm jackplugg - 2ch 48KHz 24-bit
- 2 x Inbyggd högtalare
- IP 65 frontpanel
- 408x259x36,5 mm
- Vesa-fäste 75mm/100mm eller panelmontering
- 2,9 kg
- Arbetstemperatur -20°C~60°C
- Matningsspänning DC 12-24V ($\leq 24,5W$ (15V))



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Driftstemperatur	:	-20°C~60°C
Forsyning	:	DC in 12~24V
IP-Tæthed	:	IP65
Kontrast	:	1000:1
Lyd	:	3.5mm - 2ch 48kHz 24-bit
Opløsning	:	1920x1080
VESA standard	:	70mm; 100mm
VGA	:	1
Vikt	:	2.9Kg
Dimensioner	:	405x259x36.5mm (LWD)

