

Embedded dator BT 4x RS232/485, 2 GB minne, Bred temperatur -20 ° C ~ 70 ° C Option (3/4G, Wifi, GPS, BT)

FEATURES

- Embedded Intel® Bay Trail-I E3825 CPU 1.91GHz
- 2GB DDR3L 1022MHz
- VGA
- Audio
- 4 x COM
- 2 x Intel GbE LAN
- 4 x USB 2.0 (2 internt, 2 externt)
- 2 x Mini PCIe + 9V ~ + 36V
- DIN-skenafäste
- OS-stöd: WIN 7 (32bit / 64bit) / 8.1 (32 / 64bit) / 10 (64bit)
- Linus support: Ubuntu 14.04, Fedora 19, Fedora 20, Rad hat Enterprise Linux 7





SPECIFICATIONS

CPU	:	Intel Bay Trail-I E3825 1.91 GHz (DUAL Core)
Chipset	:	Intel BAY Trail-I E3825
USB	:	4 x USB 2.0 (2 x external + 2 x internal)
Driftstemperatur	:	-20°C ~ 70°C, mSATA 70°C / 2.5" HDD 60°C
BIOS	:	Insyde UEFI BIOS
Ethernet	:	2 x Intel 10 / 100 / 1000 Mbps
Grafik	:	Intel's 7th generation (Gen 7) graphics and media encode / decode engine, Supports DX*11, OpenGL 3.0 (OGL 3.0), OpenCL 1.2 (OCL 1.2), OpenGLES 2.0
Hukommelse	:	2GB Onboard 1066MHz
Lyd	:	High Definition Audio Specification, Support Line-out / Mic-in. Amplifier Is option
OS SUPPORT	:	WIn 7 (32/64bit) Win 8.1 (32/64bit), win10 (64 bit),Ubuntu 14.04, Fedora 19, Fedora 20, Rad hat enterprise linux 7
Porte	:	4 X RS232/485 (1 have option for RS232/422/485)
SATA	:	1 x SATA ports 2.0 Data transfer rates up to 3.0 Gb/s (300 MB/s) (Share with Full Size mSATA) 2 x mini card socket for mSATA





Svensk Binär Teknik

EPC-BT-DIN

SPECIFICATIONS

Watchdog	:	Hardware Watch Dog Timer, 0~255 sec programmable
Vikt	:	0.75kg
Dimensioner	:	64H x 140W x 92D mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.