

ESW8G-DT-UN

8 Portar Gigabit switch 10/100/1000 DIN -40-75 ° - Unhaneaged, 12-48VDC, 24VAC

FEATURES

- Unhaneaged 8 ports 10/100/1000Mbit switch
- 1.5Mbits SRAM packet buffer
- IP30 metal case
- DIN-skena och väggmonteringsdesign
- 40 till 75 grader C-driftstemperatur
- 12 till 48V DC input (strömförsörjning ingår ej)



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Buffer	:	1.5Mbits SRAM packet buffer
Input	:	12~48V DC (strømforsyning er ikke inkluderet)
Kabel	:	10/100/1000BASE-T: Cat3, 4, 5, 5e, 6 UTP cable (100 meters, max.) EIA/TIA-568 100-ohm STP (100 meters, max.)
Luftfugtighed	:	5% to 95% (non-condensing)
Montering	:	DIN rail kit and wall-mount
Porte	:	8 x 10/100/1000BASE-T
Standarder	:	IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet, IEEE 802.3ab Gigabit Ethernet, IEEE 802.3x Full-Duplex Flow Control, IEEE 802.3az Energy Efficient Ethernet
Strømforbrug	:	6.72 watts
Vikt	:	461g
Dimensioner	:	135 x 87 x 32 mm

