

15 "LCD-monitor, IP66 främre, IP20 bak, Multi-touch, 1280x1024, DVI-I, VGA, 24 VDC (18 till 30 V), 1000-nits, 4: 3

FEATURES

24 "TFT-metallskärm med kapacitiv beröring, IP66, IP20
LED-bakgrundsbelysning
Kapacitiv beröring (PCAP), 4 poäng
1280 x 1024
Kontrast: 700: 1, & nbsp; 1000 nits
Visningsvinkel: 160 ° / 140 °
1 x DVI-I (29-stifts DVI-D-kontakter kvinnliga)
1 x VGA (15-polig D-sub-kontakthona)
1 x RS-232 (DB9 hane)
1 x Valfri RS232 / 422/485
Tillförsel: 100 till 240 VAC, 24 VDC (18 till 30 V)
Skrivbord, Panelmontering
6,100 g, 429 x 387 x 75 mm
-40 till 70 ° C
CISPR 32, FCC del 15B klass A - Valfritt: RS-232:
Tx D, Rx D, RTS, CTS, DTR, DSR, DCD, GND <
Valfritt: RS-422: Tx +, Tx -, Rx +, Rx -, GND
Valfritt: RS-485-2w: Data +, Data, GND
Valfritt: RS-485-4w: Tx +, Tx -, Rx +, Rx, GND





SPECIFICATIONS

Driftstemperatur	:	-40 to 70°C
Antal farver	:	16.7M (8-bit/color)
I/O	:	1 x DVI-D, 1 x VGA
IP-Tæthed	:	IP66, front IP20, rear
Kontrast	:	1000 cd/m2, 700:1, 4:3
Luftfugtighed	:	5 to 95% (non-condensing)
Porte	:	RS-232/422/485 ports x 1, software-selectable (terminal block)
Touch	:	Multi touch, 4 points
Vikt	:	6,100 g
Dimensioner	:	429 x 387 x 75 mm

