



Isolerad USB till RS485-omvandlare, -25 ° C ~ +75 ° C

FEATURES

- USB till RS485-omvandlare, isolerad
- 1 x RS485 7-polig terminalblock
- 1 x USB-B
- Hastighet: 300 ~ 115200 bps
- För USB 1.1 / 2.0 (High Speed)
- 2500 VDC-isolering på RS485
- till DIN-skena montering
- Ingen extern strömförsörjning krävs
- Input +5 VDC från USB-port
- OS-stöd WIN 98 / ME / 2000 / XP (32 / 64- bit) / Vista (32/64-bitars) / 7 (32/64-bitars) / 8 (32/64-bitars) / 10 / Linux
- Driftstemperatur. -25 ° C ~ +75 ° C
- USB-kabel (1,8m) ingår



SPECIFICATIONS

USB	:	Fully Compliant with the USB 1.1/2.0 (High Speed)
Driftstemperatur	:	-25 °C ~ +75 °C
Övrig	:	Power and data flow indicator for troubleshooting
Forsyning	:	No External Power Supply required
Hastighed	:	300 ~ 115200 bps
Isolation	:	2500 VDC Isolation Protection on the RS-485 side
Montering	:	Tiny packaging fits on your DIN-Rail
OS SUPPORT	:	Driver Supports Windows 98/ME/2000/XP (32/64-bit)/Vista (32/64-bit)/ 7 (32/64-bit)/8 (32/64-bit)/10/Linux
Stik	:	RS-485: Removable 7-Pin Terminal Block USB: Type B
Dimensioner	:	(W x H x D) 52 mm x 87 mm x 27 mm

