



Svensk Binär Teknik

ANR-LNP-800AGH

8-port industriell Gigabit-omkopplare med PoE +, ostyrd, 12-36VDC

FEATURES

- 8 x 10/100 / 1000Base-T (X) RJ45
- PoE (P.S.E.) porter
- IEEE 802.3at
- Upp till 30 watt per Port
- 9,6Kbytes Jumbo Frame
- Matningsspänning: 12 ~ 36VDC
- Auto-Negotiation & Auto-MDI / MDI-X
- Store-and-Forward Transmission
- Flow Control
- IP-30 kabinett
- DIN-skena och väggmontering
- UL klass I, Division 2 Certifierad



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Driftstemperatur	:	STD: -10° to 60°C
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Luftfugtighed	:	5% to 95%, (non-condensing)
Montering	:	DIN-skinne og væg montering
Netværk	:	10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6
PoE	:	V+, V+, V-, V-, for pin 1, 2, 3, 6 (End span, MDI-X Alternative A)
Porte	:	8 x RJ45, 10/100/1000BaseTx (PSE: 30W/Port) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
Standarder	:	IEEE 802.3 10Tx Ethernet IEEE 802.3U 100Tx Fast Ethernet IEEE 802.3ab 1000Tx Gigabit Ethernet IEEE 802.3x Flow Control for Full Duplex IEEE 802.3at/af PoE (Power-over-Ethernet)
Strømforbrug	:	10 Watts (no PD included)
Strømforsyning	:	12-36VDC Redundant input, PoE output 30W @ 12~36VDC (per PoE port)
Dimensioner	:	41.0 x 144.3 x 94.9 mm

