



Utomhus RFID-läsare med Poe, IP65, IP67 med 1 x relä. 125khz em, 13.56MHz Mifare

FEATURES

Utomhus RFID-läsare 125kHz EM 13,56 Hz
MIFARE, MIFARE Plus, DESFire / EV1 Felica
IP65, IP67
vandal säker IK08
Supporter upp till 200.000 användare
1 GHz CPU till 4 GB flash
+ 64MB RAM Multi summer
Driftstempereatur: -35 - 65 C
Vikt: 144g
Mått: 48 x 145 x 27 mm | RS-485 master eller slav
10/100 Mbps Ethernet
1 x Relä
PoE
Matningsspänning spänning~~POS=HEADCOMP:
12V DC





SPECIFICATIONS

CPU	:	1 GHZ
Driftstemperatur	:	-35°C ~ 65°C
Forsyning	:	DC 12 V / DC 24 V
Hukommelse	:	4 GB Flash + 64 MB RAM
Indgang	:	200,000 bruger kan oprettes
IP-Tæthed	:	IP65, IP67
LED	:	Flere farver
Luftfugtighed	:	0% ~ 95%, non-condensing
Netværk	:	10/100 Mbps, auto MDI/MDI-X
PoE	:	Supported (IEEE 802.3af compliant)
Porte	:	RS485, 1ch Master or Slave (Selectable)
Relæ	:	1 x Relæ





Svensk Binär Teknik

ADGANG-RFID-POE

SPECIFICATIONS

Vikt	:	Device: 144g, Bracket: 30g (Including washer and bolt)
Dimensioner	:	48 x 145 x 27



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.