

X550-T2 Intel X550AT2 Chipset 10Gb/5Gb/2.5Gb/1Gb Ethernet-adapter, PCI-E 3.0 x4 2-portars RJ45-kontakt NIC

FEATURES

- Intel X550 chipset
- PCIe v3.0 (8.0GT/S)
- Automatisk förhandling mellan 1GbE, 2,5GbE, 5GbE och 10GbE
- 2 x RJ45-portar
- Standard Cat 6 nätverkskablar
- RJ-45 Kategori-6 upp till 55 mm, Kategori-6A upp till 100m
- Stöd för Windows 64 bitar (7, 2008 R2, 8, 2012, 8.1, 2012 R2, 10, 2016
- Linux(RHEL6.x/7.x, SUSE11.x/12.x, Ubuntu*14.x/16.X) FreeBSD





SPECIFICATIONS

Chipset	:	Intel® Ethernet Controller X540
Data	:	100 Mbps / 1 Gbps / 10 Gbps
Indgang	:	RJ45 Copper
Kabel	:	10GBASE-T • 100 m on Cat 6A • 55 m on Cat 6 1000BASE-T 100 m on Cat 5e, Cat 6 or Cat 6A 100BASE-T 100 m on Cat 5e, Cat 6 or Cat 6A
OS SUPPORT	:	Server 2003 / Server 2008 / Vista / Win 7 / Win 8 / Win 10 32-64bit Windows Server 2003 / 2008 / 2008 R2 / 2012 / 2012 R2 /2016 R2 FreeBSD, Linux Stable Kernel, VMware ESX/ESXi
Protokol	:	IEEE 802.3ad (link aggregation control protocol), IEEE 802.3 2005 flow control IEEE 802.1Q VLANs, IEEE 802.1p
Protokol	:	control protocol (TCP), User Datagram Protocol (UDP), Internet Protocol (IP))
RAID niveau	:	PCI Express *2.1 (5.0 GT/s) X8 Lane operable in x8 and x16 slots

