

Intel® 9th / 8th genen Core™ i7 / i5 / i3 Compact Fläktlös dator med 6x GbE 4x COM-portar FEATURES

- CPU-stöd Intel® 9:e / 8:e-Gen
- Upp till 64 GB DDR4 2666/2400 SDRAM
- 2x SATA, 1 x M.2 NVMe, 1x full storlek mSATA
- Arbetstemp. -25 ° C ~ 60 ° C
- 1x PCIe x16 Gen3, 1x fullstora mPCIe
- 6x Gigabit Ethernet-portar
- 4x USB 3,1 Gen2, 4x USB 3,1 Gen1
- 1x VGA, 1x DVI-D , 1x DisplayPort
- 8V till 35V DC-ingång





SPECIFICATIONS

CPU	:	Supporting Intel® 9th/ 8th-Gen CPU (LGA1151 socket, 65W/ 35W TDP)
Chipset	:	Intel® Q370 Platform Controller Hub
USB	:	4x USB 3.1, 4x USB 3.1
Driftstemperatur	:	-25°C til 60°C
Chok/Vibration	:	Operating, MIL-STD-810G, Method 514.6, Category 4, Operating, MIL-STD-810G, Method 516.6, Procedure I, Table 516.6-II
Forsyning	:	1x 3-pin pluggable terminal block for 8V to 35V DC input
Grafik	:	Integrated Intel® UHD Graphics 630
Hukommelse	:	Up to 64 GB DDR4 2666/ 2400 SDRAM (two SODIMM slots)
Luftfugtighed	:	10% ~ 90% , non-condensing
Lyd	:	1x 3.5 mm jack for mic-in and speaker-out
Montering	:	Wall-mount mounting bracket
Netværk	:	6x Gigabit Ethernet ports by 1x I219 and 5x I210





Svensk Binär Teknik

EPC-IXGEN9+

SPECIFICATIONS

Porte	:	2x RS-232/422/485, 2x RS-232 ports
SATA	:	2x internal SATA port for 2.5"
Vikt	:	4.5 Kg (including CPU, GPU, memory and HDD)
Dimensioner	:	240 mm x 225 mm x 111 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.