



Trådlös hanedhållen streckkodsläsare för datainsamling

FEATURES

ST STM32 32-bitars CPU med 512K Program flash
RAM
2M byte SRAM (1 MB uppslagstabell), 4M Bytes
Flash RAM (För Font) Review 1 MB eller 35.000
poster Seite 128 x 128 punkter grafiskt FSTN LCD-
display med blå bakgrundsbelysning
Dual färg (röd / grön) LED-indikator
RS232 och USB virtuella RS232 Seite 120 ~ 80
avsökningar per sekund
uppladdningsbart litiumbatteri Pack (1700 mAh /
3.7V)
3.0V, 18mAh, Maxell ML, uppladdningsbart
litiumbatteri för SRAM
Driftstimmar: Upp till 24 timmar och 28.000
skannar
Certifieringar: FCC / CE / WEEE / RoHS
Vikt: 175 g
dimensioner: 145 x 64 x 31
drifttemperatur: 0 ° C ~ 45 ° C
OS Support: Windows-baserad (98 / Me / 2000 / XP /
Vista / Win 7 / Win 10)





SPECIFICATIONS

CPU	:	ST STM32 32 bit CPU, with 512K Program flash RAM
Driftstemperatur	:	0°C ~ 45°C
Batteri	:	Rechargeable Lithium Battery Pack (1700 mAh/3.7V)
Batteri	:	3.0V, 18mAh, Maxell ML, Rechargeable Lithium battery for SRAM
Batteri	:	Over 24 hours and more than 28,000 scans (LCD Backlight Off)
Chok/Vibration	:	1.2m drop onto concrete
Data	:	1 MB or 35,000 records
Data	:	120~80 scans per second
Hukommelse	:	2M Byte SRAM (1MB lookup table), 4M Byte Flash RAM (For Font)
Interface	:	Standard RS-232 & USB virtual RS-232
LED	:	Dual Color (Red/Green) LED Indicator
Lyd	:	Software programmable audio indication, 1KHz to 4KHz, low power transducer type.





SPECIFICATIONS

Programmerbar	:	Windows-base Application Generator
Skærm	:	128 x 128 graphic dots FSTN LCD display with blue back light
Tastatur/mus	:	21 rubber key including alphanumeric keys, function keys, and scan trigger key
Type	:	Visible Laser diode operating at 640~660 nm
Vikt	:	175g
Dimensioner	:	145 x 64 x 31mm

